

Lighting Global Product Testing Verification ovCamp Solar Home Systems

Expiration Date: September 30, 2019¹

Verify here: www.lightingglobal.org/products/omni-ovcamp

This verifies that the ovCamp Solar Home Systems product family was tested according to the Quality Test Method in the latest edition of IEC 62257-9-5, or the Lighting Global Quality Assurance Protocols for Solar Home System Kits, as applicable.² The product family **met** the Lighting Global Quality Standards.³ The product family includes the following kits:



HS2-36_LB1122, HS2-36_LBxxxxxx, HS2-72_LBxxxxxx, HS2-108_LBxxxxxx, HS2-144_LB2244, HS2-144_LBxxxxxx, HS2-180_LBxxxxxx, HS2-36_LBxxxxxx_PILOT, HS2-36_LBxxxxxx_MB200, HS2A-36_LBxxxxxx_PILOT, HS2A-36_LBxxxxxx_MB200, HS2-72_LBxxxxxx_PILOT, HS2-72_LBxxxxxx_MB200, HS2A-72_LBxxxxxx_PILOT, HS2A-72_LBxxxxxx_MB200, HS2-108_LBxxxxxx_PILOT, HS2-108_LBxxxxxx_MB200, HS2A-108_LBxxxxxx_PILOT, HS2A-108_LBxxxxxx_MB200, HS2-144_LBxxxxxx_PILOT, HS2-144_LBxxxxxx_MB200, HS2A-144_LBxxxxxx_PILOT, HS2A-144_LBxxxxxx_MB200, HS2-180_LBxxxxxx_PILOT, HS2-180_LBxxxxxx_MB200, HS2A-180_LBxxxxxx_PILOT, and HS2A-180_LBxxxxxx_MB200

Testing Details:

Product Name: ovCamp Solar Home Systems
 Model Number: See list above
 Company Name: Omnivoltaic Energy Solutions Co., Ltd.
 Country of Origin: China
 Company Contact: Alpha Guo, sales@omnivoltaic.com
 Original QTM Sample Size: n=4 or 6, as required by the applicable test method
 Renewal Test Conducted: yes
 Sample Procurement Method: Random warehouse sampling
 Testing Laboratory: Shenzhen Academy of Metrology and Quality Inspection, Shenzhen, Guangdong, China and Schatz Energy Research Center, Arcata, CA USA

These SKUs are interpreted as follows. In **HS2y-ZZ_LBxxxxxx_P**,

- y: can be blank or A, and is used to represent torch included with the kit or not ;
- ZZ: can be 36, 72, 108, 144 or 180 and is used to represent different battery capacity;
- xxxxxx: each x can be either 1, 2, 3, 4 or blank, and is used to represent the type and number of light bulbs (1 W, 2 W, 3 W or 4 W) included with the kit. For example, LB1122 includes two 1 W bulbs and two 2 W bulbs.
- P: can be Lighting Global verified products like the ovSolar PILOT or ovSolar MB200 or blank

¹ Lighting Global requires re-testing every two years or upon major product revisions, and in special cases reserves the right to grant an extension on results validity.

² www.lightingglobal.org/quality-assurance-program/

³ www.lightingglobal.org/quality-assurance-program/our-standards/

Lighting Global Product Testing Verification

ovCamp Solar Home Systems

Expiration Date: September 30, 2019¹

Verify here: www.lightingglobal.org/products/omni-ovcamp

Documentation:

Specifications book with verified test results and original version of this verification:

<http://www.lightingglobal.org/products/omni-ovcamp>

Specifications sheets with verified test results for selected systems within this product family:

<http://www.lightingglobal.org/products/omni-ovcamphs136>

<http://www.lightingglobal.org/products/omni-ovcamphs1144>



Russell Sturm

Global Head, Energy Access

Lighting Global Project Manager

International Finance Corporation

Type Approval

ovCamp Solar Home Systems

Expiration Date: September 30, 2019¹

Verify here: www.lightingglobal.org/products/omni-ovcamp

| Category | Quality Standard | Verdict |
|-----------------------------|---|---------|
| Truth In Advertising | Manufacturer accurately specified | Pass |
| | Product Name and Model Number accurately specified | Pass |
| | Performance and Component Ratings accurately specified. Any description of the product that appears on the packaging, inside the package and in any media shall be truthful and accurate. No statements shall mislead buyers or end users about the utility of the product. Numeric ratings must deviate no more than 15% from actual performance (note that it is acceptable for actual performance to exceed advertised performance). | Pass |
| Lumen Maintenance | Average relative light output \geq 85% of initial light output at 2,000 hours with only one sample allowed to fall below 75% OR All 6 samples maintain \geq 95% of initial light output at 1,000 hours | Pass |
| AC-DC Charger Safety | Any included AC-DC charger carries approval from a recognized consumer electronics safety regulator | n/a |
| Battery Composition | No battery may contain cadmium or mercury at levels greater than trace amounts | Pass |
| Battery Protection | Protected by an appropriate charge controller that prolongs battery life and protects the safety of the user. 5 out of 6 samples must meet the requirements outlined in Lighting Global Quality Standards. | Pass |
| Battery Durability | The average capacity loss of 6 samples must not exceed 25% and only one sample may have a capacity loss greater than 35% following the battery durability storage test as defined in IEC/TS 62257-9-5 Annex BB* *This product also meets the Battery Longevity requirement described in KS 2542:2014: the measured capacity after storage is at least 80% of the measured capacity before storage; no more than 1/6 samples fail | Pass |
| Physical Ingress Protection | Minimum IP2X for all products, IP3X for PV modules, and IP5X for fixed integrated outdoor products | Pass |
| Water Ingress Protection | Degree of protection required is based on product type: Fixed separate (indoor): No protection required Portable separate: Occasional exposure to rain Portable integrated: Frequent exposure to rain Fixed integrated (outdoor): Permanent outdoor exposure PV modules: Outdoor rooftop installation | Pass |

Type Approval Continued ovCamp Solar Home Systems

Verify here: www.lightingglobal.org/products/omni-ovcamp

| Category | Quality Standard | Verdict |
|---------------------------------------|--|---------|
| Drop Test | Fixed separate (indoor): No requirement All other products: 5 out of 6 samples are functional after drop test; none result in dangerous failures | Pass |
| Soldering and Electronics Workmanship | Pass soldering and electronics inspection; the maximum prevalence of bad solder joints, poor wiring or overall workmanship failure is 1 out of 6 samples in each category | Pass |
| Mechanical Durability | 5 out of 6 samples are functional after Switch, Connector, Gooseneck and Strain Relief tests; none result in dangerous failures | Pass |
| Minimum Warranty Terms | Accurately specified and consumer-facing; minimum coverage of at least one year on manufacturing defects under normal use, including the battery. Detailed requirements are specified in the Lighting Global Quality Standards | Pass |
| Performance Reporting | Light output and the corresponding solar run time are reported on the product packaging for at least the brightest setting | Pass |
| | Impact of mobile phone charging on product performance is qualitatively described on packaging | Pass |

Additional details on the requirements listed above are provided in the Lighting Global Quality Standards, available here:
www.lightingglobal.org/quality-assurance-program/our-standards/

All Quality Standards above are evaluated based on test methods described in the latest edition of IEC/TS 62257-9-5 for kits in the product family with peak power ratings less than or equal to 15 W.

Kits in the product family with peak power ratings greater than 15 W are evaluated based on the Lighting Global Quality Assurance Protocols for Solar Home System Kits and found to meet the Lighting Global Quality Standards for SHS Kits.